

SUGGESTED SPECIFICATION & CONFIGURATION

- 1. SERIES: (XXXXXX-X-XXXX)**
RFCRFF-E-ARSM - Reverse Flow Fan Filter Unit with HEPA Filter (Ceiling Mounted Unit)
- 2. MOTOR: (X)**
4 - 120V EC Motor
5 - 208/240V EC Motor
6 - 277V EC Motor
- 3. CONTROL TYPE: (X)**
1 - Adjustable Face Control
- 4. FRAME: (XXX)**
F23 - Lay-in T-Bar
- 5. PANEL: (XX)x(XX)**
24"x24"
24"x48"
- 6. FILTER: (XXXX)**
HEPA - 99.99% @ 0.3 Micron
ULPA - 99.9995% @ 0.12 Micron
- 7. INSULATION: (X)**
I - External 1.5" Foil Backed
- 8. ACCESSORIES: (XX) (XX) (XX)**
00 - None
PM - Constant Filter Monitoring
PL - Filter Pressure Light
03 - Challenge / Pressure Ports
- 9. FINISH: (XX)**
90 - 304 SS Casing with 304 SS Diffuser Screen, Polished Satin
4A - Antimicrobial White

- 1. SERIES: (XXXXXX-X-XXXX)**
RFCRFF-E-ARSM - Reverse Flow Fan Filter Unit with HEPA Filter (Mobile Unit)
- 2. MOTOR: (X)**
4 - 120V EC Motor
- 3. CONTROL TYPE: (X)**
1 - Adjustable Face Control
- 4. FRAME: (XXX)**
MBU - 3" Swivel Casters w/ (2) Brakes
- 5. PANEL: (XX)x(XX)**
24"x48"
- 6. FILTER: (XXXX)**
HEPA - 99.99% @ 0.3 Micron
ULPA - 99.9995% @ 0.12 Micron
- 7. ACCESSORIES: (XX) (XX) (XX)**
00 - None
PM - Constant Filter Monitoring
PL - Filter Pressure Light
03 - Challenge / Pressure Ports
- 8. FINISH: (XX)**
90 - 304 SS Casing with 304 SS Diffuser Screen, Polished Satin
4A - Antimicrobial White