

1100, 1190 SERIES

Diffuser | Perforated, Architectural, Curved Blade



ENGINEERING SPECIFICATION & CONFIGURATION

1190, 51190

The perforated face return diffuser shall be Krueger model 1190 (steel perforated face and backpan) or 51190 (aluminum perforated face and backpan). The diffusers shall have a perforated face with 3/16" diameter holes on 1/4" centers resulting in a 51% free area. The perimeter of the perforated face and backpan shall be an aluminum extrusion resulting in an aesthetic appearance. The diffuser shall have a tapered backpan made up of four individual pieces resulting in a square neck.

The perforated face must be easily removable from the backpan for access to the damper.

Optional opposed-blade damper (OBD) shall be constructed of heavy gage steel. Damper shall be operable from the face of the diffuser.

PERFORMANCE

The manufacturer shall provide published (printed or electronic) performance data for the diffuser. Performance data shall include 2 - 7 octave band sound power levels. The diffuser shall be tested in accordance to the data standards at the time of product introduction or ANSI/ASHRAE Standard 70.

FINISH

The paint finish shall be #44 British White and be an anodic acrylic paint, baked at 315°F for 30 minutes. The paint thickness shall be 0.8 - 1.0 mils, gloss at 60° per ASTM D523-89 of 50 - 85%, pencil hardness per ASTM D3363-92A of HB - H, crosshatch adhesion per ASTM D3359-83 of 4B - 5B, impact per ASTM D2794-93 of direct impact >100 in/lb and reverse impact >80 in/lb, salt spray per ASTM B117-9048 of 96 hours, humidity per ASTM D2247-92 of >500 hours and water soak per ASTM D870-92 of 250 hours.

1. SERIES: (XXXXX)

1190 - Perforated, Steel Return Diffuser
51190 - Perforated, Aluminum Return Diffuser

2. PATTERN: (XX)

90 - Return

3. WIDTH: (XX) *

6" - 24" in 2" Increments

4. HEIGHT: (XX) *

IF WIDTH =

6" - Select 6"
8" - Select 8"
10" - Select 10" or 22"
12" - Select 12" or 24"
14" - Select 14"
16" - Select 16"
18" - Select 18"
20" - Select 20"
22" - Select 22" or 46"
24" - Select 24"

5. FRAME: (XXX)

F22 - Surface Mount - Curved
F23 - Lay-in T-Bar
F27 - Spline

6. PANEL: (XX)x(XX)

NONE
12"x12"
12"x24"
24"x24"
24"x48"

7. DAMPERS: (XX)

00 - No Damper
01 - Steel Opposed Blade Damper (Model OBD)
15 - Aluminum Opposed Blade Damper (Model 5OBD)

8. ACCESSORIES: (XX)

00 - No Accessories
S - Straightening Grid

9. FINISH: (XX)

01 - Mill
03 - Black Backpan with British White Face
10 - Alumican
35 - Black
44 - British White

* See chart on page C1-103 for available neck sizes.

SAMPLE CONFIGURATION: 51190 - 90 - 12x24 - F22 - NONE - 00 - 00 - 10