

# 9700, 9700A, 9700D

Stainless Steel Supply Grilles, Sightproof



## ENGINEERING SPECIFICATION & CONFIGURATION

### 9700

The door grille shall be a Krueger model 9700. This grille shall have 20 gage, 304 stainless steel louvered blades spaced no further than 1" apart to provide a sight-proof barrier. The frame of the grille must be constructed of 20 gage 304 stainless steel and have countersunk screw holes. This frame must also produce a border of 1 3/8" around all sides of the grille with mitered corners.

### 9700A

Model 9700A is the same as 9700 but comes with a 18 gage 304 stainless steel auxiliary frame for mounting on the back side of the door grille.

### 9700D

Model 9700D is the same as 9700 but comes with a second core and frame constructed of 304 stainless steel with 20 gage louvered blades and 18 gage frame for mounting on the back side of the door grille to provide a sight-proof barrier.

Optional 316 stainless steel construction available.

### FINISH

The finish shall be 90 - #4 Satin Polish, obtained by finishing with a 120-grit abrasive, or 44 - British White.

#### 1. SERIES: (XXXXX)

9700 - Single Core Door Grille  
9700A - Single Core Door Grille with Auxiliary Frame  
9700D - Double Core Door Grille

#### 2. PATTERN: (X)

H - Horizontal Front Blades  
V - Vertical Front Blades

#### 3. WIDTH: (XX)

4" - 48" in 1" Increments

#### 4. HEIGHT: (XX)

4" - 60" in 1" Increments

#### 5. MATERIAL: (XXX)

304 - Stainless Steel Grade 304  
316 - Stainless Steel Grade 316

#### 6. FINISH: (XX)

90 - #4 Satin Polish  
44 - British White

SAMPLE CONFIGURATION: 9700 - H - 12x12 - 304 - 90