


6400 (Supply)

6490 (Return)



6600 (Supply)

6690 (Return)

**Introduction: 6400, 6600 Series**

The 6400/6600 series perforated diffusers uses modular air pattern controllers mounted to the backside of the perforated face, which are factory set for 4-way air pattern. They are field adjustable for 1, 2, or 3-way pattern or may be removed for down blow without reducing the core area. The 6400/6600 series diffusers exhibit typical isothermal throws of 12' to 17' for 4-way air distribution and 21' to 30' for 1-way air distribution. The modular capability makes the 6400/6600 ideal for installations with changing air pattern requirements such as tenant lease spaces. Matching returns are the 6490 and 6690 series.

**MODELS**

- 6400 - Steel, Square Neck Supply Diffuser
- 6490 - Steel, Square Neck Return Diffuser
- 56400 - Perforated Aluminum with Steel Backpan, Square Neck Supply Diffuser
- 56490 - Perforated Aluminum with Steel Backpan, Square Neck Return Diffuser
- 6400FR - Steel, Fire Rated, Square Neck Supply Diffuser
- 6600 - Steel, Round Neck Supply Diffuser
- 6690 - Steel, Round Neck Return Diffuser
- 56600 - Perforated Aluminum with Steel Backpan, Round Neck Supply Diffuser
- 56690 - Perforated Aluminum with Steel Backpan, Round Neck Return Diffuser
- 6600FR - Steel, Fire Rated, Round Neck Supply Diffuser

**FEATURES**

- Field adjustable 1, 2, 3, or 4-way blow patterns.
- Great choice for installations with changing air pattern requirements.
- Removable perforated face for easy cleaning.

**PANEL SIZES**

- 12"x12"
- 16"x16"
- 20"x20"
- 12"x24"
- 24"x24"
- 24"x48"

**ACCESSORIES**

- Optional Opposed Blade Damper (Model OBDFA)
- Optional Round Dampers
- Optional Insulated Backpan

**FINISHES**

- Standard finish is #44 British White.
- Optional finishes available.